

1 ABERDEEN FOAM

1% AFFF-LF-C6

LOW FREEZE AQUEOUS FILM FORMING FOAM



An internationally accredited, high quality Low Freeze Aqueous Film Forming Foam (AFFF-LF) concentrate which is compliant with the EPA 2010/15 PFOA Stewardship Programme (see below).

Designed to quickly extinguish and secure Class B hydrocarbon fires of liquids such as crude oil, gasoline, aviation kerosene and fuel oil. Formulated for use with either fresh or seawater.

Not suitable for use on fuels which are polar solvents and water miscible such as alcohols, ketones, aldehydes and ethers.

HOW IT WORKS

Aberdeen Foam 1% AFFF-LF-C6 effectively extinguishes and secures liquid hydrocarbon fires by the following actions:

Film forming – the foam forms an aqueous film across the surface of the fire to quickly cut off the oxygen supply and effectively knock down the flames.

Low surface tension – as the liquid drains from the foam, the surface tension reduces to ensure the foam floats on top of the surface of the liquid fuel.

Foam expansion – the foam cools the fuel's surface and creates a stable blanket to suppress the release of flammable vapours.

Resealing – if the blanket is broken by personnel or equipment, the foam quickly reseals to minimise the risk of re-ignition.

FIRE PERFORMANCE APPROVALS

The requirement to meet the EPA 2010/15 Stewardship Programme has resulted in a reformulation of our range of foam concentrates (see below).

We are pleased to announce that Aberdeen Foam 1% AFFF-LF-C6 concentrate has been tested in 2013 and is Internationally accredited to:

- Underwriters Laboratory UL 162

C6 & THE EPA 2010/15 PFOA STEWARDSHIP PROGRAMME

All traditional Fire Fighting Foams contain fluorosurfactants. Fluorosurfactants aid fire extinguishment and support excellent burnback properties.

However, a USA EPA working group has found that fluorosurfactants containing R_f carbon chain length greater than C6 could potentially degrade in the environment and form PFOA, a chemical which is bioaccumulative, toxic and persistent.

Due to this discovery, in 2005 the EPA convened what has come to be known as the **2010/15 PFOA Stewardship Programme**. Under this programme, all fluorosurfactant manufacturers worldwide have committed to withdraw from sale any fluorosurfactant with a carbon chain length greater than C6 by 2015.

In the Fire Fighting Foam manufacturing industry, this means that all manufacturers are required to reformulate and retest their foam concentrates by 2015.

Aberdeen Foam 1% AFFF-LF-C6 has been developed and specially reformulated to meet the requirements of the 2010/15 PFOA Stewardship Programme.

For further information, please contact Oil Technics Ltd.



1% AFFF-LF-C6

PHYSICAL PROPERTIES

Appearance	Clear pale straw liquid
Specific gravity	1.04
pH at 20°C	7 - 8
Viscosity @ 20°C mPas	~4
Surface tension @ 20°C N/m	0.019
Freezing point (°C)	< -20
Lowest use temp. (°C)	-17.8
Expansion*	≥ 6:0
25% drainage (minutes)	≥ 3.0
Max. storage temp.(°C)	49
Min. storage temp.(°C)	-17.8
Freeze/thaw effect	None

* Foam quality will depend on the foam equipment used and the operating conditions. The above are tested in accordance with UK Defence Standard 42-40.

FOAMING PROPERTIES

Foam expansion properties will vary depending on several factors including:

- Using salt or fresh water
- Water hardness
- Equipment characteristics
- Equipment flow rate

For example, aspirating devices will produce typical expansion ratios of between 6:1 and 10:1 and non-aspirating devices between 2:1 and 4:1.

Always check your equipment's operation manual for guidance.

ENVIRONMENTAL IMPACT

- Contain no fluorosurfactants of chain length greater than C6
- Biodegradable
- Butyl carbitol free
- Low fluorine content (typical value: 1.5% fluorine)
- Low toxicity to aquatic organisms

APPLICATIONS

Aberdeen Foam 1% AFFF-LF-C6 concentrate provides quality protection wherever hydrocarbons present a fire risk:

- Offshore platforms and helidecks
- Petrochemical refining, processing and storage facilities
- Marine terminals, power stations and road / rail loading racks
- Rapid Intervention Vehicles and aircraft hangar systems

Produced AFFF-LF foams can also be used as wetting agents for combating Class A fires (i.e.tyres, paper, wood) and for providing a vapour suppression blanket on hydrocarbon spills.

PROPORTIONING EQUIPMENT

Aberdeen Foam 1% AFFF-LF-C6 concentrate is readily proportioned with the following equipment:

- In-line inductors (fixed or portable)
- Balanced pressure variable flow proportioners
- Around the pump proportioners
- Bladder tank Balanced Pressure proportioning skid
- Handline, aspirating nozzles with fixed inductor pickup tube

DISCHARGE EQUIPMENT

Aberdeen Foam 1% AFFF-LF-C6 concentrate is suitable for use with:

- Foam chambers
- Aspirating and non-aspirating sprinklers or spray nozzles
- Water fog nozzles for handlines and monitors
- Foam makers for use with either Floating Roof or Bund Protection systems

PROPORTIONING INFORMATION

- 1 part foam concentrate to 99 parts water

STORAGE AND SHELF LIFE

Best stored as supplied in original, unopened containers. Suitable for storage in containers and tanks manufactured from:

- Stainless steel (Type 304L or 316L)
- High density cross-linked polyethylene
- RFP – vinyl ester epoxy resin only

Aberdeen Foam 1% AFFF-LF-C6 concentrate is designed for use in cold climates and has low minimum use and storage temperatures.

If kept in the original manufacturer's supplied container and stored between -17.8°C and 49°C, a shelf life of at least 10 years can be expected.

To prolong the shelf life of any AFFF-LF, do not expose to temperature extremes and prevent contamination from foreign materials.

COMPATIBILITY

Our laboratory tests have shown Aberdeen Foam 1% AFFF-LF-C6 concentrate is compatible in all proportions with other high quality low freeze aqueous film forming foams and ABC and BC fire fighting powders.

However, in order to maintain EPA 2010/15 compliancy, it is recommended that **C6 foams are not mixed with any other foams.**

As recommended by NFPA 11, we would advise that if mixing foam concentrates from different manufacturers a compatibility study is carried out beforehand.

Different types of foam concentrates - for example AFFF and Protein Foams - should never be mixed.

For further information or advice on compatibility testing, please contact Oil Technics Limited.

DISPOSAL

Produced Aberdeen Foam 1% AFFF-LF-C6 can be safely disposed of in biological waste water treatment systems.

INSPECTION AND TESTING

As recommended by NFPA11, BS:EN 13565-2:2009 and BS 5306, Aberdeen Foam foam concentrates should be inspected and tested at least annually as part of your fire fighting foam maintenance programme.

Oil Technics Limited offers a worldwide foam testing service and inhouse foam testing training. For further details, please contact us or visit our website: www.foamtesting.com

TECHNICAL SERVICES AND SALES SUPPORT

For our UK customers, Aberdeen Foam is available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515

Aberdeen Foam is manufactured in Scotland under ISO 9001 and ISO 14001 accredited management systems and audited by UL every four months.

PACK SIZES

Available in the following sizes:
20 litre, 25 litre, 200 litre, 1000 litre containers and bulk tanks

Oil Technics Ltd reserve the right to modify any specification at any time and without prior notice.



Manufactured & supplied by
Oil Technics (Fire Fighting Products) Ltd
Linton Business Park, Gourdon,
Aberdeenshire, Scotland UK DD10 0NH

T: +44 (0) 1561 361515
E: info@firefightingfoam.com

F: +44 (0) 1561 361001

W: www.firefightingfoam.com www.foamtesting.com

